



ROCKFON Blanka®

ROCKFON Blanka®

- ROCKFON Blanka has a deep-matt, smooth, super-white surface with high light reflection and light diffusion, contributing to energy savings and a bright and comfortable indoor environment.
- ROCKFON Blanka's smooth, non-directional surface reduces installation time and the anti-static surface withstands exposure to worksite dust.
- The enhanced surface durability makes ROCKFON Blanka more resistant to dirt and everyday wear and tear, enhancing the product lifetime.



Impact Resistance

Class 3A (Fastening clip)
Impact resistance of ROCKFON Blanka with edge Z or M mounted with fastening clip has been tested in accordance with EN13964 – Annex D and approved as Class 3A.

PRODUCT DESCRIPTION

- Stone wool tile
- Visible side: deep-matt, smooth and super-white painted fleece
- Rear side: back fleece
- Durable painted edges

ASSORTMENT

Edge detail	Module size (mm)	Weight (kg/m ²)
A15	600 x 600 x 20	2.3
	1200 x 600 x 20	2.3
A24	600 x 600 x 20	2.3
	1200 x 600 x 20	2.3
B	600 x 600 x 20	3.4
	1200 x 600 x 20	3.4
D	600 x 600 x 20	3.4
	1200 x 600 x 20	3.4
	1800 x 600 x 20	3.4
	900 x 900 x 25	4.1
	1200 x 300 x 20	3.4
Dznl/A100	1200 x 600 x 20	3.4
	1500 x 600 x 20	3.4
	1500 x 300 x 20	3.4
	1800 x 300 x 20	3.4
	1800 x 600 x 20	3.4
	2100 x 300 x 25	4.1
	2100 x 600 x 25	4.1
	2400 x 300 x 25	4.1
	2400 x 600 x 25	4.1
	1200 x 300 x 20	3.4
	1200 x 600 x 20	3.4
	1500 x 300 x 20	3.4
	1500 x 600 x 20	3.4
	1800 x 300 x 20	3.4
1800 x 600 x 20	3.4	
Dznl/A24	2100 x 300 x 25	4.1
	2100 x 600 x 25	4.1
	2400 x 300 x 25	4.1
	2400 x 600 x 25	4.1
	1200 x 300 x 20	3.4
	1200 x 600 x 20	3.4
	1500 x 300 x 20	3.4
	1500 x 600 x 20	3.4
E15	600 x 600 x 20	2.8
	1200 x 600 x 20	2.8
E24	600 x 600 x 20	2.8
	1200 x 600 x 20	2.8
G	600 x 600 x 20	3.4
	1200 x 600 x 20	3.4
M	600 x 600 x 20	3.4
	1200 x 600 x 20	3.4
X	600 x 600 x 22	3.7
	1200 x 600 x 22	3.7
	1800 x 600 x 22	3.7
Z	600 x 600 x 20	3.4
	1200 x 600 x 20	3.4

Other dimensions are available on request. Please contact ROCKFON.




PERFORMANCES



Sound absorption

α_w : 1,00 (Class A)



Reaction to fire

A1



Light reflection and light diffusion

87% light reflection
>99% light diffusion



Humidity and sag resistance

Up to 100% RH



Cleaning

- Vacuum
- Damp cloth
- Wet-scrub resistance Class 1

The wet-scrub resistance is tested in accordance with EN ISO 11998:2007, rated on a scale from 1 to 5, where 1 is best.



Hygiene

Stone wool provides no sustenance to microorganisms



Visual appearance

Super-white surface
L value: 94.5

The whiteness (L value) of the product is tested in accordance with ISO 7724 and measured on a scale from 1 (black) to 100 (white).

Deep matt surface, perfect in critical side-light
Gloss: 0.8% at 85° angle

The gloss of the product is tested in accordance with ISO 2813.



Surface durability

Enhanced durability and dirt resistance.



Environment

Fully recyclable



Indoor environment

A selection of ROCKFON products have been awarded



We believe our acoustic stone wool and metal solutions for ceilings and walls are a fast and simple way to create beautiful, comfortable and safe spaces.

Easy to install and durable, they protect people from noise and the spread of fire. They are our way of making a constructive contribution towards a sustainable future.

Create and Protect is what drives us. It means putting people first, sharing success and maintaining trust.

It's our rock-solid promise to you. At ROCKFON, Create and Protect is what we do – and it's inspired by you.

ROCKFON Middle East

(Affiliate of ROCKFON / ROCKWOOL B.V., The Netherlands)

Office 136, JAFZA 16

P.O. Box 61082

Jebel Ali, Dubai

UNITED ARAB EMIRATES

Tel.: +971 4 8818179

Fax: +971 4 8818180

www.exp.rockfon.com

rockfonme@rockfon.com